

ALEXB PROGRAMS MANUAL

SP79 German Mastering Console GE



Alessandro Boschi
Verbania - Italy
www.alex-b.eu

Copyright © 2009 All Rights Reserved

ABOUT ME

AlexB is a one-man company, so:

Hi ! I'm Alex :)

I have been a member of the Acustica Audio community since the 2007, and started Beta-Testing in 2009. I released my first commercial program libraries for Nebula Pro in 2009 because I wasn't satisfied by the sound of the plugins.

What I looked for was a good emulation of the console to improve my music - I have composed a lot of songs for Café del Mar in that years. My first Café del Mar recording was done with a Korg CR-4 only, then the following years I have moved to PC world and Nebula has been found as the plugin of my dreams.

Sincerely at the first test I wasn't satisfied at all by the sound. The libraries was very poorly sampled and the plugin was a little cloudy and flat.

After being in touch with Giancarlo (the genius behind Acustica Audio) and to have said him about my thoughts about what to improve in Nebula, he has promptly given me a new improved release of the plugin. We have continued for the whole afternoon and after some exchanges of test and new releases, finally Nebula became dynamic, open, deep and with life. Thank you Giancarlo !

So, pushed by this experience I've made some of the most highly sought after and rare hardware devices available for use in the digital world while maintaining virtually all of the analog character that makes recording a true art-form. Every sampled hardware piece has been refurbished and modified to improve the sonic characteristics, thanks to my 30+ years of experience in electronics and audio engineering. With hyper-realistic samplings of pristine mastering equalizers, top class consoles, the most sought after compressors, and the rarest vintage devices, I'm proving to the audio community that Acustica Audio sets the standard for the finest sound quality in the digital realm by facilitating a true analog experience with programs that make full use of the VVKT technology.

Please visit the website for more information: <http://www.alex.eu>

Thank you !

AlexB... Audio Renaissance.

NOTICES

Please do not illegally share the program libraries, your financial support allow me to continue in developing. **Be aware: there isn't any authorized reseller of my programs.**

Disclaimer

This manual provides general information, preparation for use, installation and operating instructions for the AlexB Programs Libraries. The information contained in this manual is subject to change without notice. AlexB makes no warranties of any kind with regard to this manual, or the product(s) it refers to, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. AlexB shall not be liable for errors contained herein or direct, indirect, special, incidental, or consequential damages in connection with the furnishing, performance, or use of this material or the product(s).

All product names used in this documentation are trademarks of their respective owners, which are in no way associated or affiliated with my company (AlexB). These trademarks of other manufacturers are used solely to identify the products of those manufacturers.

End User License Agreement (EULA)

By installing the software you confirm your acceptance of the AlexB End User License Agreement, as well as the AlexB terms of service and privacy policy which can be found at:

www.alex-b.eu/terms_and_conditions.html

www.alex-b.eu/privacy_policy.html

This AlexB End-User License Agreement is between AlexB and you.

IMPORTANT – PLEASE READ THIS LICENSE AGREEMENT CAREFULLY BEFORE INSTALLING THIS SOFTWARE.

By using the AlexB software you accept these terms. If you do not accept these terms, do not use the Software.

1. Limited Use License.

The Software is licensed, not sold, by AlexB or Acustica Audio to the original end user for use only on the terms set forth in the Agreement. If and only if your Software is purchased through AlexB or Acustica Audio, AlexB, as Licensor, grants you, as an end user Licensee, a non exclusive license to use the Software. The customer purchases the right to license the use of the programs, not the actual ownership of a copy of the program. That means no sharing, copy or resell. User can install the software on two computers and he can make a personal backup copy.

2. Title.

The Software is owned by AlexB and is Software is protected by copyright and other intellectual property laws. AlexB retains title to and ownership of the Software and all copies, as well as any

rights not specifically granted. This Agreement only gives you certain rights to use the Software and related documentation, which may be revoked if you do not follow these terms.

3. Limited Rights to Install and Use the Software.

You may install the Software into the memory of two computers for your internal business use or your own personal enjoyment, but may not redistribute or electronically transfer the Software to someone else's computer or operate it in a time-sharing or service-bureau operation.

You may make one copy of the Software for backup purposes only. You may not modify, translate, adapt, reverse engineer, decompile, create other works from, or disassemble the Software or any portions thereof. Similarly, you may not copy, modify, adapt, transfer, or create other works based upon the printed materials and "online" or electronic documentation accompanying or published for use with the Software (the "Documentation"). You are free to edit and save new presets for your own use, and not to distribute to others. If you make an alteration to a preset that you like and find it useful, please save it as a new preset for your own use. The Software may include technological measures that are designed to prevent or detect unlicensed use of the Software. Circumvention of these technological measures is prohibited. Any attempt to circumvent technical limitations may render the Software or certain features unusable or unstable, and may prevent you from updating or upgrading the Software.

4. Export, Renting and Transfer Restrictions.

You may not export, convey, rent, sublicense, or otherwise distribute the Software or any rights therein to any person or entity. You may not transfer or resell your Software license.

5. Warranty and Support.

Neither AlexB nor Acustica Audio warrant that the software will meet your requirements or that its operation will be uninterrupted or error free, in the same way the use or the results of the use of the Software or documentation in terms of their correctness, accuracy, reliability.

Technical support is for customers only. You can ask support via email or web form and receive a reply at least into 24 hours.

Thank you

Documentation, Installation and Support

Introduction

Thank you for purchasing the AlexB library programs for Nebula.

Now you have one of the best professional high quality audio software. I have spent countless hours to develop these no-compromise programs to give you only the best sound and the most realistic "feel" as possible to the real hardware. I'm confident that this plugin will help you make better and more professional mixes (while enjoying yourself even more)... Because: Sound First !

If you have any trouble with the software please do not hesitate to contact me at:

support@alexb.eu

Overview

Despite the digital revolution in the pro audio industry, many of today's top albums are still mixed on analog consoles and with analog outboard gear. Mixing into an analog desk just sounds better. Everything sits better in the mix, there is more weight to the bottom, and the overall sound is more three dimensional.

Analog devices produce electrical artifacts that affect frequency response, add harmonics, cause signal clipping and increase noise. These artifacts, which audio engineers often consider the character of a particular device, result from a combination of factors such as component grade, technology type (i.e. vacuum tubes, ICs, transistors), power supply specifications, equipment casing and other variables.

Depending on the circuit characteristics, input signal frequency response varies. Some circuits cut frequencies, others boost them. This behaviour is part of the overall device character and should not be confused with user adjustable EQ.

Total harmonic distortion (THD) is based on the levels of the odd and even harmonics of an input signal, usually at a level much lower than the fundamental level. THD balance and decay are circuit dependent, and thus differ from device to device.

Cross-Talk and Noise are two elements which every designer tends to avoid to not affect the audio quality. Since in the analog world they can't be avoided, fortunately in digital domain with Volterra Technology I have reduced the noise at less of -120dBfs and completely avoided Cross-Talk during the sampling.

The result is an optimum full quality sound from a like-new working condition hardware.

I have recreated these non linearity characteristics into these programs by sampling the units in excellent condition. Your tracks will become more alive with the classic vibe of a real hardware and you may notice that your mixes may take on an almost magical quality with punch, glue, and dimension that you didn't hear with your other algorithmically based plugins.

Sampling Process

I believe that "Vectorial Volterra Kernels Technology" is the path of the future and will enable analog sound to be implanted into digital DAW environments with real harmonic content and analog vibe. In my creation of these Nebula Programs, I use only top notch modern and vintage gear, precisely sampled by using my own proprietary technique with custom converters I have built specifically for NAT3 which outperforms top notch commercial converters. Ultra filtered and stable AC supply, high end cables, with particular care to the connections, levels and impedance matching were used to translate the sonic qualities of this priceless devices into the Nebula software technology. Every captured sample is analyzed and carefully listened. Every volume change, gain change, frequency change is tested and accurately programmed without destructive digital processing for optimized sound and then compared to the original device. The result is a virtually indistinguishable digital replication of this landmark device.

The hardware is sampled without introduction of noise or aliasing. The thinking behind this process is to provide the full quality of the analog behavior, which means placing all emphasis on quality over cpu resources. The process is extremely efficient and optimized to be used on current computer technology with a forward thinking to the future of more powerful systems, but this will be a more cpu-intensive device than your typical software. Consider the value in having even one instance of the original unit in your hardware rack and choose to see the true value in having the best sound that technology has to offer.

The preset doesn't sound processed, harsh or digital as many plugins do, but instead it sounds like a natural extension of the original audio, gluing your tracks in the mix with an analog vibe.

Some plugins make your recordings sound like digital.

Some plugins are supposed to make your recordings sound like analog.

THIS plugin helps make recordings sound like MUSIC !

System Requirements

- Intel or AMD CPU based PC or MAC computer
- Free space on Hard Disk or better SDD (library size depending)
- Nebula3 v1.3.903 or Nebula4 with installed commercial license

Installation and file BACKUP

After downloading, unpack the files and **make a safe backup** of the library. I recommend to use a Toshiba Canvio 2.5" HD as well to do a regular backup of your system with Acronis True Image.

Copy the files manually, *.N2P into \programs folder and *.N2V into \vectors folder.
Clean the \temp folder in the main root nebulateprepository.

The Skin

Skins for Nebula3 and Nebula4 have a cost but they are included in the libraries as **gift**.

To install the skin into Nebula3:

- 1 - copy the *.N2S file into the root skin folder
- 2 - run your DAW and open Nebula
- 3 - go into MAST Page
- 4 - set the Skin to ALEXB_N3
- 5 - click on save and reload Nebula

To install the skin into Nebula4:

- 1 - copy the *.N2S file into the root skin folder
- 2 - copy the Properties files into Properties root folder
- 3 - run your DAW and open Nebula
- 4 - load a preset

After installation it's recommended to clean the \nebulateprepository\temp folder.
Now you are ready to go at the next step to read how to use your new Nebula library!

Remember:

Scientific studies have proven that the brain is influenced more by the visual stimuli than acoustics.
What you see is not what you hear. In mixing and mastering nobody can hear your screen.

General Use

Parameter Settings

Some parameters must to be set into Nebula to work correctly with AlexB Programs.

Nebula3

The best way is to make copy-and-paste of Nebula3.dll and Nebula3.xml (or whatever is the name of your installed Nebula plugin has) then rename both copies as AlexB-N3.dll and AlexB-N3.xml.

Now set the following parameters by editing the AlexB-N3.xml file:

```
<AHEADLENGTH> 6000 </AHEADLENGTH>  
<RATECONVERSION> 4500000 </RATECONVERSION>  
<OFREQD> 11 </OFREQD>  
<SKINNAME> ALEXB_N3.N2S </SKINNAME>  
<DSPBUFFER> 8192 </DSPBUFFER> (optional for better audio quality)
```

click on save and load the AlexB-N3 in your DAW.

Nebula4

The best way is to make copy-and-paste of N4.dll and N4.xml then rename both copies as AlexB-N4.dll and AlexB-N4.xml.

Now set the following parameters by editing the AlexB-N4.xml file:

```
<AHEADLENGTH> 5000 </AHEADLENGTH>  
<OFREQD> 11 </OFREQD>  
<OTIMED> 5 </OTIMED>  
<LEDSPEED> 3 </LEDSPEED>  
<DSPBUFFER> 8192 </DSPBUFFER> (optional for better audio quality)
```

click on save and load the AlexB-N4 in your DAW.

NOTE: MAC users find more info on the “MAC Nebula4 Setup Addendum” on the website:
www.alexeb.eu/nebula/AlexB_MAC_Nebula4_Setup_Addendum.pdf

Off Line Process

If your DAW isn't powerful or you want/need to freeze or export processed audio tracks I strongly recommend the Free NEBULASETUP2 by Zabukowski: <http://zabukowski.com/software/>

Gain Staging

GUI's meters show the value in dBfs.

Take care with gain staging since the programs are close to the hardware, as reference 0dBVU on the hardware corresponds to -18dBFS on your DAW digital meter.

Normally the best sound is achieved with occasional maximum digital peaks to -10dBfs, i.e. kick or snare transients, pluck synth and other hits. On the mixbus the whole mix can hit an occasional maximum digital peaks between -8dBfs and -6dBfs. (imperative!)

When the signal is too high the sound will be congested and saturated/distorted in a bad way, too high peaks (and inter-sample peaks) overload Nebula which plays a BLIP as alert.

I recommend to mix with a good and precise VU Meter like this by Waves:

<https://www.waves.com/plugins/vu-meter>



It mimics the way our ears react to sound by giving you a more realistic representation of the way audio level changes are actually perceived.

In this way you can easily check the levels on every single track and for the whole mix by inserting the VUMeter as last instance on the mixbus and by setting the 0dBVU = -18dBfs on it (Headroom).

I suggest to deactivate or remove the VU Plugin when you export the mix to avoid any coloration. Yes, some plugins color the sound even if they are analyzers and/or bypassed.

NOTE: a console, limiter, equalizer, tape machine or compressor is not a guitar amp! If you drop the level back to where it would be using the real hardware, libraries can sound huge.

Useful video about to use the VU Meter and Gain Staging:

https://www.youtube.com/watch?v=2DVz_T48M-Q

<https://www.youtube.com/watch?v=ECRx4WF3pcc>

Great book about audio recording engineering:

<https://bobbyowsinski.com/recording-engineers-handbook/>

Another great book about music production with my contribution about console:

<https://www.routledge.com/Producing-Music-1st-Edition/Hepworth-Sawyer-Hodgson-Marrington/p/book/9780415789226>

Common Controls

All programs have some common controls which are detailed below.

Input Gain

The Input Gain control sets the level at the input of the plugin.
The range is from $-\infty$ dB to +6 dB.

Output Gain

The Output Gain control sets the level at the output of the plugin.
The range is from $-\infty$ dB to +6 dB.

Bypass

This switch control sets the plugin operative or bypassed

Meters

Input and Output Meters display the levels at the input and output of the plugin in dBfs.
Compressors and Expander/Gate have a gain reduction meter also.

NOTE: *clicking on the controls while pressing "ctrl" on computer keyboard, the control returns to zero.*

SP79 German Mastering Console – Golden Edition

About the original hardware

The legendary sound of the 1980's era was mastered with this German console which makes program audio sound better just by passing through it's circuits. When you shape your sound with this console the results will be fantastic, regardless of musical style.

The unit has been completely refurbished and returned to the original as new conditions. This technical intervention restores the unit to the original sound and it can then rightfully be called "vintage". It's the same sound you can listen on thousands old hit records.

The most critical, and most difficult task is to refurbish the unit without making changes to the original character and sound. This is achieved by the thoughtful choice of the right electronic components, and expert skills and experience in electronic engineering.

With its amazing sound the SP79GE German Mastering Console has been engineered to deliver recordings at the best conceivable quality onto any format at any sample rate, capturing all the energy and atmosphere of the original performance as perfectly as possible.

Session Setup

SP79GE Console reproduces the sound of Vintage German Mastering Console by using a library programs consisting of channels input, group bus and mixbus. To faithfully reproduce into the DAW the analog console signal chain and workflow, we recommend using the SP79GE Console in one of two following session setup configurations.

As a virtual summing box : Input Channel is inserted on the last insert of the DAW audio tracks, like a direct out routed to a summing box. The MixBus is placed on the first insert of the master track, just as the stereo return would be routed from the analog console back to the DAW.

To simulate a console : Input Channel is inserted on the first insert of the DAW audio tracks, the MixBus is placed on the last insert of the master track. If you group channels in your DAW, i.e. drums elements, you can insert the GroupBus as last insert in the submix group bus to achieve the classic bus coloration.

TRICK: *to emulate the non linearity between the channels of the console, you can set the GDRV control slightly different on every track into a range of +/-3dB.*

Preset list:

The SP79GE Console library includes 18 different programs:

HQ presets with 10 kernels and LE presets with 3 and 5 kernels displayed into sub-menu "P79"

SP79GE Filters: High and Low Pass stepped combo Filters – 20, 30, 40Hz / 16, 18, 20kHz 18dB/Oct.

SP79GE Input Clean : input channel modern clean tone

SP79GE Input Vintage : input channel aged tone

SP79GE M.Bus Clean : MixBus modern clean tone

SP79GE M.Bus Chocolate : MixBus warmth tone

SP79GE M.Bus Creamy : MixBus glue tone

SP79GE M.Bus Vintage : MixBus aged tone

SP79GE M.Bus Vanilla : MixBus natural clean tone

SP79GE M.Bus Air : MixBus with patched the famous "Swiss" Linear Phase eQ

SP79GE Filters

Stepped Combo Filters, HPF and LPF

SP79GE Input Clean

The Input Clean is the first stage of the console, normally it works as line amplifier and you should insert it in every track. Input and output transformers are present in the audio path.

SP79GE Input Vintage

The Input Vintage it's the "aged" line input and has more coloration than Input Clean, you can use it when more character is needed. Input and output transformers are present in the audio path.

NOTE: *don't use any Input preset if you need a clean and neutral sound.*

SP79GE M.Bus Clean

SP79 Console Mix Bus is the final stage of the console, it must be inserted in the mixbus of the DAW. The M.BUS Clean gives a modern clean finished sound.

SP79GE M.Bus Chocolate

When the warm tone is needed, use the M.BUS Chocolate preset as last insert into DAW's mixbus.

SP79GE M.Bus Creamy

When a polished glued mix is needed try the M.BUS Creamy preset as last insert into DAW's mixbus.

SP79GE M.Bus Vintage

When the classic "aged" tone is needed, use the M.BUS Vintage preset as last insert into DAW's mixbus.

SP79GE M.Bus Vanilla

When the natural and clean tone is needed, use the M.BUS Vanilla preset as last insert into DAW's mixbus.

SP79GE M.Bus Air

When the clean and airy tone is needed, use the M.BUS Air preset as last insert into DAW's mixbus.

Controls

The SP79GE Console has only a few but intuitive and effective controls which are detailed below.

GDrive Control

GDRV

The "GDRV" control is a unique feature not found in similar products from others brands that comes from Acustica Audio VVKT proprietary technology and sampling approach. It allows you to control the amount of harmonic distortion that is coming from the analog hardware. The "Input" control acts as the analog signal chain of the device, where reducing the volume also reduces the harmonic distortion in accordance. The "GDrive" function allows independent control of this harmonic content, so that the input level can be left alone while making adjustments to the harmonics. Reducing the harmonics leads to a cleaner signal with an already clean device. Increasing the harmonics should be done with moderation. This type of effect is not truly representative of a real console, but it can be useful when you want more of the console's nonlinear "vibe" without altering the channel's levels. The available range is ± 12 dB.

Note that increasing the input signal the internal headroom will be reduced.

THD Control

THD

The "THD" control affects the harmonic contents in an unnatural way, but suitable if you look for an effect. Increasing the value for a fat and saturated sound, lowering the value for a thin and detailed sound.

NOTE: clicking on the controls while pressing "ctrl" on computer keyboard, the control returns to zero.

NOTE2: do not adjust the ATTCK and RELS controls, leave them at stock value (center 12 o'clock).

END